SPECTRUM

M

Innovative design with monitor and built-in keyboard, large casters and handles on the sides of the equipment make the 6040 M ideal for events and places that require mobility and ease of installation. The Spectrum 6040 M uses 160KV or 180KV X-ray generators that meets the highest standards of image quality and penetration for even faster and more efficient inspection.





For a safer world



STANDARD FUNCTIONS

- · Automatic discrimination of organic, inorganic and mixed materials by colorization
- · Automatic image saving
- Baggage counter
- Continuous scanning
- Zoom higher than 128x • Color or black / white image
- Edge highlight
- High penetration function
- Sharpness
- TIP threat image projection
- · High density alert

- · JPG, TIFF, BMP and VMI image export
- Network connection
- · Real-time scanning
- Self-diagnosis system
- Color inversion
- Real-time image manipulation
- · Automatic detection algorithm for drugs, explosives and high density materials
- Storage capacity over 200,000 images

SAFETY

Dose lower than $1\mu Sv / h$ at 0.1m away from equipament

OPTIONAL FUNCTIONS AND ACCESSORIES

- · Customized painting
- · Training software
- Local language
- Remote workstation
- ASTM standard test kit
- Modular roller table
- · Lockable anti theft console with key
- Remote management software for multiple devices
- Camera
- Tunnel protection extension
- Ability to integrate with conveyor system
- WiFi capability
- Integration with Garrett's walk-through metal detector
- ONVIF compatibility

SHIPPING CRATING SIZE AND WEIGHT

Product Spectrum	Package	Length	Width	Height	Net Weight	Gross Weight
6040 M	1 Box	1460mm	1000mm	1380mm	490 kg	580 kg




5PECTRUM 6040 M

- 1636(L) / 880/1211(W) / 1333(H) [mm] 64.4" (L)/ 34.6"/47.7"(W) / 52.5"(H)
- 490kg | 1080.3lbs
- Operating temperature and humidity: 0°C to 40°C / 5% to 95% (non-condensing)
- -40°C to 60°C / 5% to 95%
- (non-condensing)
- 110 127VAC / 208 240VAC (-15% to +10%); 50Hz/60Hz, +/-3Hz
- 740VA

GENERAL SPECIFICATIONS

- 619mm (W)/424mm (H) 24.4" (W)/16.7" (H)
- 0.22m/s
- 755mm | 29.7"
- · Maximum load on the conveyor: 160kg | 352.7lbs
- 160kV operating at 150 kV
- 180kV operating at 170 kV

- 40AWG
- 42mm | 1.6" (150kV) 44mm | 1.7" (170kV)
- High resolution (configurable size)
- Insulating oil
- Diagonal upward
- * Specification according to Test Piece VMI









1101 Brickell Avenue, South Tower, 8th Floor Miami, FL - USA Postal code: 33131 Phone: +1 305 779 5692 www.vmisecurity.com

X-RAY SCANNERS











